

ATTESTATION OF CONFORMITY

Issued to: Havells India Ltd.
ORG Towers, 2D, Sector 126, Noida Expressway, NOIDA - 201304, INDIA

For the product: PV Inverter

Trade name: **HAVELLS**

Type/Model: enviro GT i3300TX, enviro GT i4400TX, enviro GT i5000TX, enviro GT i5500TX
enviro GT i6600TX, enviro GT i8800TX, enviro GT i11000TX, enviro GT i12000TX

Ratings: See Annex

Manufactured by: Havells India Ltd.
ORG Towers, 2D, Sector 126, Noida Expressway, NOIDA - 201304, INDIA

Requirements: IEC 60255-27:2013 (Second Edition)

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 6066884.51.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

Arnhem, 25 November 2019

Number: 6066884.02AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kate Xu
Certification Manager



© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2

DEKRA Testing and Certification (Shanghai) Ltd.

3F #250 Jiangchangsan Road Building 16 Headquarter Economy Park Shibe Hi-Tech Park, Jing'an District, Shanghai 200436 China
T +86 21 6056 7600 F +86 21 6056 7555 www.dekra-certification.com

Ratings of the test product:

enviro GT i3300TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 3000 W, max 3300 VA, max 3x4.8 A

enviro GT i4400TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 4000 W, max 4400 VA, max 3x6.4 A

enviro GT i5000TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 5000 W, max 5000 VA, max 3x8.0 A

enviro GT i5500TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 5000 W, max 5500 VA, max 3x8.0 A

enviro GT i6600TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 6000 W, max 6600 VA, max 3x9.6 A

enviro GT i8800TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 8000 W, max 8800 VA, max 3x12.8 A

enviro GT i11000TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 10000 W, max 11000 VA, max 3x15.9 A

enviro GT i12000TX:

PV input: Max.1000 Vdc, MPPT voltage range: 160-960 Vdc, max 11/11 A, Isc PV: 14/14 A

Output: 400V, 3/N/PE, 50/60 Hz, nominal 12000 W, max 13200 VA, max 3x19.1 A